



Enriching Lives


KIRLOSKAR BROTHERS LIMITED



iHT Series

INNOVATIVE SPLIT CASE PUMPS

Your Preference, Our Innovation



Energy Efficient | Dual Drive | Compact Design | Leakage Proof | Low Downtime

INNOVATIVE-iHT SERIES
HORIZONTALLY SPLIT CASING PUMP

Kirloskar Brothers Limited (KBL) is a leading manufacturer of horizontal split case pumps. Over the years we have taken feedback from our customers and understood their needs and converted them into an innovative design - iHT. iHT is a 2900 rpm horizontal axially split casing, centrifugal pump with new features.

iHT is available in single and double stage construction backed up with maintenance friendly design and with optimum efficiencies. This new generation split case pump is designed for externally removable type bearing housing, DIN cavity mechanical seal, impeller nut & sleeve arrangement and easy wear ring fitment. These pumps have a lot of maintenance friendly features apart from operational advantages like dual drive.



Single stage



Two stage pump

BENEFITS

- Highly efficient - low operation cost
- Compact size and less floor space
- Low down time - quickly fixable
- Low prime mover cost
- Lowest pumping - project cost
- Dual Drive to reduce downtime

PUMP DETAILS

Delivery Sizes : Upto 300 mm
 Discharge : 30-1300 m³/hr
 Head : 30 to 250 Metres
 Speed : 2900 rpm
 Stuffing Box : Mechanical Seal for Single stage
 Mechanical Seal / Gland packing for double stage.
 Flanges : As per BS 4504 PN16/PN25/PN40
 Liquid Temperature : 8.0°- 90° C
 Material : CI Casing/BR Impeller/SS431 Shaft



APPLICATION

- Suitable for Fire fighting
- Primary & secondary HVAC application
- High pressure boosting system
- Dewatering in mines
- Cooling tower
- Recirculation
- Industrial utility water application
- Desalination
- Water supply
- Paper plant
- Steel plant for high pressure injection
- Sugar plant

CONSTRUCTIONAL FEATURES

iHT pumps are horizontal split case single/double stage centrifugal pumps. All single stage pumps are provided with double suction type impeller. Both single stage/double stage pumps are fitted with DIN 24960 cavity mechanical seal. The impeller/s is/are centrally placed on a sturdy designed shaft and the entire rotating assembly is dynamically balanced to provide a smooth, trouble free, longer and efficient operation.

FLANGES

All single stage pumps are designed for flanges as per BS 4504 PN16 & PN25 rating and for two stage pumps flanges are as per BS 4504 PN40 rating. For other standard flange requirements, please contact us.

SPECIAL FEATURES

EASY BEARING REMOVAL

The bearing can be removed without dismantling the upper half casing and without taking the rotating unit out by using puller. Thus, saving on the down time and cost.




iHT Series

Your Preference, Our Innovation



SIMPLE TO REPLACE THE WEAR RING

iHT is designed for easy dismantling and assembly. Hence, with average fitment skills casing ring can be replaced.




Top view lower half casing (conventional way)

Top view lower half casing (innovative way)

FOOLPROOF ASSEMBLY OF IMPELLERS

Both impellers are designed in such a way by using Pokayoke that they cannot be wrongly fitted in each other's place.



First stage impeller

Second stage impeller

BETTER HEAT DISSIPATION, ENHANCED GREASE LIFE

Special Engineering plastic UHMWPE is used for bearing caps in order to achieve higher resistance to corrosion and changes in the weather condition.

Because of its better heat dissipation, rise in temperature is reduced in bearing housing which helps in enhancing the grease life.



Bearing caps

DUAL DRIVE, REDUCED DOWNTIME

iHT series is designed for dual drive i.e., the pump can be connected to motor and engine & can be switched over by clutch arrangement. This helps in reducing the downtime as well as the need for a stand by pump.

Since the pump can be driven from both the ends, it provides flexibility for attaching it with prime mover having clock wise or anti-clockwise rotation to suit the site requirements.



Dual Drive

REDUCTION IN ASSEMBLY TIME DUE TO INNOVATIVE SLEEVE AND NUT ARRANGEMENT

Due to the robust design and construction, vibrations are within limit as per HIS standard.

iHT series has been designed to provide ease in replacing worn-out sleeves without disturbing the impeller assembly.




Conventional method of impeller & nut arrangement

Conventional method of impeller & sleeve arrangement

Innovative method of impeller, nut and sleeve arrangement

HT FAMILY RANGE AT 50Hz



- Note: 1) i-HT05AA, i-HT06AA, i-HT12XD, i-HT15XE, i-HT15XF ARE TWO STAGE PUMPS
 2) MAXIMUM FLOW IS TAKEN UPTO 8 Mtr NPSHR
 3) COLOR GROUP INDICATING INTERCHANGEABILITY OF MAJOR COMPONENTS

As we are constantly endeavouring to improve the performance of our products/ equipment, we reserve the right to make alterations from time to time and as such our products/ equipment may differ from that detailed in this publication. For latest information you may get in touch with our Regional Sales Offices.



Enriching Lives

Pumps | Valves | Motors | Hydro Turbines | Turnkey Projects

Let's celebrate the spirit

KIRLOSKAR BROTHERS LIMITED

Corporate & Marketing Office : "Yamuna", Survey No. 98 / 3 to 7 Baner, Pune - 411 045 (India)
 • Phone: +91 - 20 - 2721 4444 • E-mail: kblin@kbl.co.in • Web Site : www.kbl.co.in

Regional Sales Offices: **India:** Ahmedabad, Bangalore, Bhubaneswar, Kolkata, Chennai, Jaipur, Kochi, Lucknow, Mumbai, Nagpur, New Delhi, Pune, Ranchi, Secunderabad

Overseas: Ajman, Cairo, Johannesburg, Nairobi, Phnom Penh, Miami, Vientiane, Bangkok, Amsterdam, Dakar